




TECHNICAL DATA

UPOFLOOR ESTRAD SAFETY

WET ROOM R11/50+



Estrad Safety R11 7750




Estrad Safety R11 7747



Estrad Safety R11 7748



Estrad Safety R11 7749














Estrad Safety R11 7751



Estrad Safety R11 7746

Estrad Safety R11/50+ has been specially developed for changing-room facilities, wet areas, shower rooms, spas, saunas, swimming pool environments, constantly damp rooms in nursing homes, student homes, specialised care, health care and special housing, i.e., for areas requiring efficient slip resistance. In wet areas, in addition to water, also where body wash and shampoo residues increase the risk of slipping.

	PROPERTY	TEST METHOD	RESULT
	Thickness	EN 428 / ISO 24346	~0.08" (2.0 mm)
	Weight	EN 430 / ISO 23997	0.55 lbs / sq ft (2700 g/m ²)
	Roll Length	EN 426 / ISO 24341	65.62' (20 m)
	Width	EN 426 / ISO 24331	6'6" (2 m)
	General Performance	EN 13845 ASTM F1303	Conforms Conforms
	Use Area	EN 685 / ISO 10874 23 / 34 / 43	
	Resistance to Chemicals	EN 423	Good chemical resistance
	Water Tightness	EN 13553 Annex A	Watertight
	Reaction to Fire	EN 13501-1 ASTM E648 Australian BCA Spec C1.10-3	Class Bfl-S1 Class 1 Complies
	Abrasion Resistance	EN 13845 EN 649	50,000 cycles Group T
	Enhanced Slip Resistance	EN 13845 AS 4586 Appendix A AS 4586 Appendix C AS 4586 Appendix D DIN 51097 DIN 51130 RRL Pendulum Test Surface Roughness	ESb & ESf P4 Class B R11 Class B R11 ≥ 50 (wet test - 4S Rubber/Slider 96) Rz ≥ 20 μm
	Electrical Behaviour (body voltage)	EN 1815	≤ 2 kV Classified as 'antistatic'
	VOC Emissions	AgBB VOC Test FloorScore Finnish M1 Classification	Pass Certified Certified