



GUARANTEED DURABILITY TO HARD WEAR PUBLIC SPACES

- Homogeneous construction
- Easy installation with minimal waste
- The product is without surface treatment
- With waxing tough, strong and long lasting flooring
- Certified Low-VOC Flooring Product
- Phthalate free & DEHP free
- Over 60 years of experience
- Manufactured in Finland

TECHNICAL DATA


Product	EN 649	Finntile
Application	EN 685: 23/34/43	Public spaces subject to hard wear

Technical Specification

Thickness	EN 428	2.0 mm
Weight	EN 430	4000 g/m ²
Tile Size	EN 427	300 x 300 mm
Delivery Package		5,4 m ²

Product properties	Test method	Result
Fire Resistance	EN 13501-1	B _n - s1
Indoor Air Certifications		M1
Impact sound insulation	ISO 140-6 / ISO 717-4	L _w n. 2 dB
Dimensional stability	EN 434	< 0.1 %
Effect of castor chair	EN 425	Suitable
Residual Indentation	EN 433	< 0.05 mm
Wear resistance	EN 660-2	T ≤ 2.0 mm ³
Colour Fastness	EN ISO 105-B02	≥ 6
Slip Resistance	EN 13893	DS (> 0,3)
Flexibility	EN 435	40 mm
Chemical Resistance		Good resistance to most acids, alkalis, and solvents
Bacterial Growth		Does not act as a substrate for bacterial growth







9701



9702



9703




9719



9721



9722




9723



9724



9725



9744



9753



9767