



HEAVY DUTY FLOORS WITH NO ENVIRONMENTAL COMPROMISE

- Designed for heavy wear public spaces: offices, department stores, shops, schools, hospitals, day care centres and retirement homes
- Durable structure
- Easy maintenance, excellent stain resistance
- Free from PVC and plasticizers
- Lively, non-directional chip design
- Virtually invisible seams
- No wax required
- Bacteria resistant and antistatic

TECHNICAL DATA

Product	EN 14565	Heavy wear public spaces
Application	EN ISO 10874	23/34/43


Technical Specification

Thickness	EN ISO 24346	2,0 mm
Weight	EN ISO 23997	3600 g/m ²
Tile size	EN ISO 24342	500 x 500 mm
Delivery packaging		5 m ² (20 tiles)

Product Properties

Property	Test method	Result
Fire resistance	EN 13501-1	B _{f1} - s1
Indoor air certifications		M1, FloorScore, Der Blaue Engel
Dimensional stability	EN ISO 23999 (50 °C/6 h)	< 0,2 %
Residual indentation	EN ISO 24343-1 (2,5 h)	< 0,05 mm
Colour fastness	EN ISO 105-B02	6
Slip resistance	EN 13893	DS (> 0,3)
Abrasion resistance	EN 660-2	Group T < 2,0 mm ³
Chemical resistance	EN ISO 26987	Excellent resistance to acids, alkalis, solvents
Electrical propensity	EN 1815	< 2 kV (antistatic)
Flexibility	EN ISO 24344	40 mm
Chastor chair effect	EN 425	Suitable
Underfloor heating		Suitable (max 28 °C)
Bacterial growth		Does not act as a substrate for bacterial growth






5010



5012



5015



5017



5018



5022



5042



5014



5016



5019



5025



5026



5043



5045



5046



5062



5064



5066



5068



5048




5051



5052



5056



5057



5058