

TECHNICAL DATA

UPOFLOOR ZERO TILE

ENOMER® CONTRACT TILE FLOORING

PRODUCT

Zero Tile	EN 14565	PVC- and plasticizer-free Enomer® flooring tile
Application	EN ISO 10874	23/34/43



SPECIFICATION

Thickness	EN ISO 24346	~0.08" (2.0 mm)
Weight	EN ISO 23997	~0.70 lbs / sq ft (3400 g/m ²)
Tile size	EN ISO 24342	~20" x 20" (500 x 500 mm)
Packaging unit		~53.8 sq ft (5 m ² , 20 tiles)

PRODUCT PROPERTIES


PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, Floorscore, Austrian Ecolabel
Electrostatic Propensity	AATCC 134	< 2.0 kV
Electrical Resistance	ASTM F 150	> 50 GΩ
Slip Resistance DCOF (Wet)	ANSI B 101.3	Acceptable
Slip Resistance SCOF (Dry & Wet)	ASTM D 2047	≥ 0.7 Dry / Wet
Abrasion Resistance w weight loss	ASTM D 4060	< 0.05 g
Castor Chair Test 25.000 cycles	EN 425	Pass
Critical Radiant Flux	ASTM E 648	≥ 0.45 W/cm ² Class 1
Smoke Density	ASTM E 662	≤ 450 Flaming & Non-flaming
Flexibility	ASTM F 137	Pass (8 mm mandrel)
Resistance to Heat	ASTM F 1514	Pass
Resistance to Light	ASTM F 1515	Pass
Short Term Indentation	ASTM F 1914	0.006" (7.06%)
Chemical Resistance	ASTM F 925	Excellence
Static Load Limit	ASTM F 970	0.001"
Static Load Limit	ASTM F 970 Mod	2000 psi




COLLECTION
UPOFLOOR ZERO TILE
ENOMER® CONTRACT TILE FLOORING




5102 CAPE COD




5103 PEWTER




5104 STONE GREY




5105 GRAPHITE




5111 SILVER GREY



5112 CONCRETE




5113 GRANITE




5122 DUSTY




5123 MOROCCO




5124 CORUNDUM




5128 MAYAN MAIZE




5129 SUNBEAM



5132 CAROTENE



5143 TERRACOTTA




5152 BLUE MOON




5154 SERENITY




5155 OZONE




5158 BLUE ORCHID



5159 DENIM



5162 THORN APPLE



5163 SPRUCE



5164 AMBROSIA



5176 CURRY