

Maintenance guide

KÄHR'S QUARTZ MOSAIC, TEMA, UNI, LINES

This document is universal instruction which can be used to create the cleaning program for the installed floorings. Cleaning program should be created by co-operation with cleaning experts paying attention to use, traffic and properties.

For best possible performance it is highly recommended to use polyester pads under furniture legs to get flooring lasting in longer.

INITIAL CLEANING

Do not use wet cleaning methods directly after installation. Adhesive must be dried properly. This can take few weeks. Remove loose dirt with a mop or vacuum cleaner. Wash the floor using a combination machine with red pads, a scrubbing machine with medium hard brushes, or a floor cleaning machine and a wet vacuum cleaner. Use a mild alkaline cleaning and maintenance agent. Rinse the floor carefully but avoid excessive use of water. Treat the cleaned floor with an SHS machine and a maintenance care agent.

INITIAL POLISHING

Initial polishing is not needed because of PUR (polyurethane) treatment.

DAILY MAINTENANCE

Alternate dry/damp cleaning with wet cleaning methods. Regular treatment with a combination machine keeps the floor clean and heavy basic cleaning can be avoided. Use a mild alkaline cleaning and maintenance agent. You can also clean the floor with an SHS machine and a maintenance agent. When necessary, cleaning with a stronger maintenance agent is recommended.

BASIC CLEANING

Basic cleaning should be performed on very soiled floors exposed to heavy traffic. Clean the floor with an alkaline or strong alkaline detergent. Use a floor cleaning machine with red or blue pads. Clean old and heavily soiled floors with brown pads. Rinse the floor carefully. Apply a maintenance care agent solution to the cleaned floor and treat the dry surface with an SHS machine. When necessary, polishing can be carried out on areas with most traffic.